



The most eco-friendly vending solution

SandenVendo owes its popularity to a reliable mechanism technology and the premium cooling units applied on each of its vending models since 1930. The Bottle&Can automatic vending machine represents a true flagship in terms of quality standards and durability: this simple yet functional column vendor today is upgraded with modern features and a user-friendly interface. In addition, always considering environmental sustainability, B&C Design Narrowstack has been developed with an HC (R290) Hydro Carbon version, pursuing the commitment to employing natural refrigerants on our vending machines.

XS-C36

Narrowstack 6

TECHNICAL SPECIFICATIONS

XS-C36

DIMENSIONS H x W x D (mm)	1830 x 650 x 800
WEIGHT (NET - Standard machine without options)	280 Kg
NO. OF SELECTIONS / COLUMNS	6
MAX. PRODUCT LENGTH (mm)	325
MAX. PRODUCT DIAMETER (mm)	72
MAX. CAPACITIES CANS 0.33 l	306
MAX. CAPACITIES PET BOTTLES 0.50 l	102
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+1°C up to +25°C
CLIMATE CLASS	N (+16°C up to +32°C)
COOLING UNIT	HC2 / HCD
POWER SUPPLY	220/240 V - 50 Hz
MAX. POWER CONSUMPTION (HCD)	320 W
ENERGY CLASS (HCD)	B
ENERGY CONSUMPTION - kWh/annum (HCD)	566

OPTIONAL

SPECIAL CODED LOCK (RIELDA)
 SAFETY SLIDE COIN INSERT
 SECURITY CASH BOX SYSTEM
 WALL/FLOOR FIXING KIT
 OUTDOOR KIT - ANTI RAIN
 PAYMENT SYSTEM
 DEX / UCS KIT
 VARIOUS FITTING KITS
 CUSTOMIZATION
 CUSTOMIZED CABINET COLOUR



The most eco-friendly vending solution

SandenVendo owes its popularity to a reliable mechanism technology and the premium cooling units applied on each of its vending models since 1930. The Bottle&Can automatic vending machine represents a true flagship in terms of quality standards and durability: this simple yet functional column vendor today is upgraded with modern features and a user-friendly interface. In addition, always considering environmental sustainability, B&C Design Narrowstack has been developed with an HC (R290) Hydro Carbon version, pursuing the commitment to employing natural refrigerants on our vending machines.

S-C47

Narrowstack 7

TECHNICAL SPECIFICATIONS

S-C47

DIMENSIONS H x W x D (mm)	1830 x 750 x 955
WEIGHT (NET - Standard machine without options)	300 Kg
NO. OF SELECTIONS / COLUMNS	7
MAX. PRODUCT LENGTH (mm)	325
MAX. PRODUCT DIAMETER (mm)	72
MAX. CAPACITIES CANS 0.33 l	476
MAX. CAPACITIES PET BOTTLES 0.50 l	238
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+1°C up to +25°C
CLIMATE CLASS	N (+16°C up to +32°C)
COOLING UNIT	HC2 / HCD
POWER SUPPLY	220/240 V - 50 Hz
MAX. POWER CONSUMPTION (HCD)	320 W
ENERGY CLASS (HCD)	B
ENERGY CONSUMPTION - kWh/annum (HCD)	507

OPTIONAL

- SPECIAL CODED LOCK (RIELDA)
- SAFETY SLIDE COIN INSERT
- SECURITY CASH BOX SYSTEM
- WALL/FLOOR FIXING KIT
- OUTDOOR KIT - ANTI RAIN
- PAYMENT SYSTEM
- DEX / UCS KIT
- VARIOUS FITTING KITS
- CUSTOMIZATION
- CUSTOMIZED CABINET COLOUR



The most eco-friendly vending solution

SandenVendo owes its popularity to a reliable mechanism technology and the premium cooling units applied on each of its vending models since 1930. The Bottle&Can automatic vending machine represents a true flagship in terms of quality standards and durability: this simple yet functional column vendor today is upgraded with modern features and a user-friendly interface. In addition, always considering environmental sustainability, B&C Design Narrowstack has been developed with an HC (R290) Hydro Carbon version, pursuing the commitment to employing natural refrigerants on our vending machines.

M-C48

Narrowstack 8

TECHNICAL SPECIFICATIONS

	M-C48
DIMENSIONS H x W x D (mm)	1830 x 850 x 955
WEIGHT (NET - Standard machine without options)	340 Kg
NO. OF SELECTIONS / COLUMNS	8
MAX. PRODUCT LENGTH (mm)	325
MAX. PRODUCT DIAMETER (mm)	72
MAX. CAPACITIES CANS 0.33 l	544
MAX. CAPACITIES PET BOTTLES 0.50 l	272
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+1°C up to +25°C
CLIMATE CLASS	N (+16°C up to +32°C)
COOLING UNIT	HC2 / HCD
POWER SUPPLY	220/240 V - 50 Hz
MAX. POWER CONSUMPTION (HCD)	320 W
ENERGY CLASS (HCD)	B
ENERGY CONSUMPTION - kWh/annum (HCD)	550

OPTIONAL

- SPECIAL CODED LOCK (RIELDA)
- SAFETY SLIDE COIN INSERT
- SECURITY CASH BOX SYSTEM
- WALL/FLOOR FIXING KIT
- OUTDOOR KIT - ANTI RAIN
- PAYMENT SYSTEM
- DEX / UCS KIT
- VARIOUS FITTING KITS
- CUSTOMIZATION
- CUSTOMIZED CABINET COLOUR



The most eco-friendly vending solution

SandenVendo owes its popularity to a reliable mechanism technology and the premium cooling units applied on each of its vending models since 1930. The Bottle&Can automatic vending machine represents a true flagship in terms of quality standards and durability: this simple yet functional column vendor today is upgraded with modern features and a user-friendly interface. In addition, always considering environmental sustainability, B&C Design Narrowstack has been developed with an HC (R290) Hydro Carbon version, pursuing the commitment to employing natural refrigerants on our vending machines.

L-C4X

Narrowstack 10

TECHNICAL SPECIFICATIONS

L-C4X

DIMENSIONS H x W x D (mm)	1830 x 1015 x 955
WEIGHT (NET - Standard machine without options)	375 Kg
NO. OF SELECTIONS / COLUMNS	10
MAX. PRODUCT LENGTH (mm)	325
MAX. PRODUCT DIAMETER (mm)	72
MAX. CAPACITIES CANS 0.33 l	680
MAX. CAPACITIES PET BOTTLES 0.50 l	340
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+1°C up to +25°C
CLIMATE CLASS	N (+16°C up to +32°C)
COOLING UNIT	HC2 / HCD
POWER SUPPLY	220/240 V - 50 Hz
MAX. POWER CONSUMPTION (HCD)	320 W
ENERGY CLASS (HCD)	B
ENERGY CONSUMPTION - kWh/annum (HCD)	577

OPTIONAL

SPECIAL CODED LOCK (RIELDA)
SAFETY SLIDE COIN INSERT
SECURITY CASH BOX SYSTEM
WALL/FLOOR FIXING KIT
PAYMENT SYSTEM
DEX / UCS KIT
VARIOUS FITTING KITS
CUSTOMIZATION
CUSTOMIZED CABINET COLOUR